



Production Tubing (API 5CT)

Production tubing for transporting oil and gas from reservoir to surface. OD 1.050" to 4-1/2", grades J55 to P110, with NUE, EUE, semi-premium and premium connections.



API 5CT

OCTG

2-3/8"–4-1/2"

J55–P110

EUE

Semi-Premium

Premium

PRODUCT OVERVIEW

Production tubing (API 5CT) transports oil and gas from the bottom of the well to the surface, typically supplied in ~9.5 m (31 ft) joints with threaded connections. IPC supplies tubing from certified manufacturers with full API 5CT dimensional and mechanical compliance.

Available in R2 (8.53–9.75 m) and R3 (11.58–12.8 m) lengths, grades J55 through P110, with EUE (external upset end), NUE (non-upset end), semi-premium and premium connections. Supplied with plastic end caps and transport supports.

TECHNICAL SPECIFICATIONS

Product	Production tubing — API 5CT, OCTG
Use	Transport oil & gas from reservoir to surface
OD	2-3/8" – 4-1/2"
Wall Thickness	3.18 – 16 mm
Length R2	8.53 – 9.75 m (standard)
Length R3	11.58 – 12.8 m
Grades	J55, K55, N80-1, N80-Q, L80, C90, T95, P110
Connections	NUE (Non-Upset), EUE (External Upset), Semi-Premium, Premium
Sour Service	C90, T95, L80 available
Protection	Plastic end caps, transport support frames

KEY FEATURES

- Full API 5CT grade range J55 to P110
- OD 2-3/8" to 4-1/2"
- NUE, EUE and premium connections
- R2 and R3 lengths
- Sour service grades available
- Full dimensional and mechanical compliance
- Drift, hydrostatic and thread gauge testing

APPLICATIONS

- Oil & gas production wells
- Water injection wells
- Gas lift completions
- Electric submersible pump (ESP) installations
- Geothermal applications

MANUFACTURER / SUPPLIER

Interpipe (Ukraine) · Certified API 5CT mills — China, Ukraine, USA

REQUEST A QUOTE

IPC CORPORATION

Pipeline · Tube · Industrial Solutions
www.ipc-corporation.com
info@ipc-corporation.com

CONTACT

USA: +1 (645) 237-7525
Colombia: +57 317 624 0319

REQUEST A QUOTE

info@ipc-corporation.com

